

RDY Servers

2U Rugged Server | 4th and 5th Gen Xeon SP[®]

A highly scalable, compact, secure, rugged rack server with the latest in high-performance computing technologies to ensure peak performance and adaptability for a variety of ever-changing applications for on-premise, cloud, and edge deployments.



DESIGN VERSATILITY FOR MAXIMUM CONFIGURABILITY

Quickly adjust your system configuration to meet the constantly fluctuating demands of diverse data environments and ensure operational efficiency.



ENHANCED COMPUTE + CONNECTIVITY

Securely process, analyze, store, retrieve, and transfer large amounts of actionable intelligence in seconds to improve decision-making and reduce response times.



RUGGEDIZED FOR EXTREMES

Tested to meet the toughest military and industrial standards to ensure the quality and reliability of our solutions within harsh and austere conditions.



Overview

A scalable, high-density 2U rugged server supporting various option cards and standard motherboard form factors that delivers maximum processing, AI/ML/DL, networking, security, and storage alongside evolving workloads.

Designed in consultation with our team, this server meets and exceeds the most complex technical, performance, and environmental requirements of your application or program.

SOLUTION HIGHLIGHTS



Intel[®] PFR, SGX, TME, and TDX provide chip-based protections of firmware, data, applications, hypervisors, and virtual machines.



Next-gen PCIe slots enable you to easily expand your board's capabilities to meet the demands of your application or program.



Reduce time to market to take advantage of the latest technologies as they become available and maximize operational efficiency.

POWERED BY 

AI ACCELERATED BY  NVIDIA.

Third-party motherboards available upon request. Reach out to a member of our team for more information.

Technical Overview

SPECIFICATION	DETAILS
CPUs	Dual Intel® 4 th and 5 th Gen Xeon®
Memory	32x DDR5-4800 ECC RDIMM slots (16x per CPU)
Storage	Up to 2x M.2 SSDs, 6x SATA/NMVe SSDs (FIPS 140-2/3 available)
Form Factors	2U rack server (19" x 3.5" x 22" 48.26cm x 8.9cm x 55.88cm)
Network Interface	1GbE port supporting IPMI
PCIe Interconnect	1x OCP x16 slot, and 4x PCIe 5.0 x16, 4x PCIe 5.0 X8 slots via MCIO connectors
Power	2x 1600W, redundant, removable

PROCESSORS (UP TO 32 CORES PER CPU)

Dual Intel® 4th and 5th Gen Xeon® SP CPU up to 270W TDP
Chipset: Intel® C741 Emmitsburg

**If an SKU higher than 270W is needed, contact a member of our team.*

MEMORY (UP TO 8 TB)

32x DDR5-4800 ECC RDIMM slots (16x per CPU)

SLOTS (CAN SUPPORT FHFL GPUs)

1x OCP x16 slot, and 4x PCIe 5.0 x16, 4x PCIe 5.0 X8 slots via MCIO connectors

I/O

- ▶ **USB:** 3x USB ports: 2x USB2 ports via I/O riser, 1x USB3 header
- ▶ **IPMI:** IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
- ▶ **Graphics:** Intel® Integrated Graphics & ASPEED AST2600 BMC
- ▶ **Video:** 1x VGA port
- ▶ **LAN:** 1GbE port supporting IPMI

SECURITY

▶ TPM 2.0

**For a comprehensive list of cybersecurity features, please contact one of our team members.*

COOLING (BMC Controlled)

8x 6 pin system fan headers, 2x 4 pin CPU fan headers

SYSTEM BIOS

- ▶ AMI SPI 256 Mbit BIOS
 - Plug and Play (PnP)
 - PCI 2.2
 - ACPI 1.0 / 2.0
 - USB Keyboard Support
 - SMBIOS 2.3
 - UEFI

SYSTEM MANAGEMENT (BMC)

ASPEED AST2600 baseboard management controller: rKVM, system monitoring, out-of-band management

OS COMPATIBILITY

- ▶ Windows Enterprise, Server
- ▶ Linux
 - RHEL
 - Ubuntu
 - SUSE

**Contact us for the full compatibilities list*

DIMENSIONS

Board: 17" x 11.5" (43.18cm x 29.21cm)

Chassis: 19" x 3.5" x 22" (48.26cm x 8.9cm x 55.88cm)

ENVIRONMENTAL SPECIFICATIONS

- ▶ Operating Temperature: -40°C - 50°C
- ▶ Storage Temperature: -40°C - 85°C
- ▶ Operating Humidity: 5°C-95°C relative
- ▶ Non-Operating Humidity: 5°C-95°C relative
- ▶ Shock: 3 axis, 15g, 11ms (MIL-STD-810)
- ▶ Vibration: 5Hz to 2,000Hz (SSD)
- ▶ Altitude: -300ft to 10,000ft
- ▶ Non-Operating Altitude: -300ft to 40,000ft

**Preliminary numbers noted. Final numbers expected to outperform current specifications.*

**Conformal coating available upon request.*

COMPLIANCE

Designed to meet the following standards/certifications:

- ▶ MIL-STD-810H
- ▶ MIL-STD-461G
- ▶ DO-160F
- ▶ MIL-STD-704

Our 2U Rugged Servers are customizable per your most complex application or program requirements. Designed to support additional customer-specified option cards including NVIDIA A/H100 Multi-Instance GPUs.

Contact us for pricing and availability.

770.287.3100 | info@trentonsystems.com