

## RDY SERVERS

# PT.1 Server | 4<sup>th</sup> Gen Xeon<sup>®</sup> SP

A highly scalable, compact, secure, rugged rack server with the latest high-performance computing technologies to ensure peak performance and adaptability for a variety of ever-changing applications.



### MAXIMUM CONFIGURABILITY, FLEXIBILITY, AND SCALABILITY

Quickly adjust your system's performance to meet the constantly fluctuating demands of diverse data environments and ensure operational efficiency.



### ENHANCED COMPUTE + CONNECTIVITY

Process, analyze, store, retrieve, and transfer large amounts of actionable intelligence in seconds to improve decision-making and reduce response times.



### RUGGEDIZED FOR EXTREMES

Tested to meet the toughest military and industrial standards to ensure the quality and reliability of our solutions within harsh and austere conditions.

## Overview

A configurable, SWaP-C optimized 1U RDY Server supporting various option cards that delivers maximum processing, AI/ML/DL, networking, security, and storage alongside evolving workloads.

Designed in consultation with our team, the PT.1 Server meets and exceeds the most complex technical, performance, and environmental requirements for on-premise, cloud, and edge deployments.



## SOLUTION HIGHLIGHTS



Intel<sup>®</sup> PFR, SGX, TME, and TDX provide chip-based protections of firmware, data, applications, hypervisors, and virtual machines.



Next-gen PCIe slots enable you to easily expand your board's capabilities to meet the demands of your application or program.



Reduce time to market to take advantage of the latest technologies as they become available and maximize operational efficiency.

POWERED BY 

AI ACCELERATED BY 

Third-party motherboards available upon request. Reach out to a member of our team for more information.

# Technical Overview

SPECIFICATION	DETAILS
CPUs	Single Intel® 4 <sup>th</sup> Gen Xeon® SP (Sapphire Rapids)
Memory	8x DDR5-4400/4800 ECC RDIMM slots
Storage	Up to 9x SATA SSDs, NVMe w/RAID controller (FIPS 140-2/3 available)
Form Factors	1U rack server (19" x 1.75" x 20"   48.26cm x 4.44cm x 50.8cm)
Network Interface	3x 1GbE, 2x 10GbE ports supporting IPMI
PCIe Interconnect	1x PCIe 5.0 x16 slot for FHFL option cards
Power	2x 500W, redundant, non-461, removable

## PROCESSORS (UP TO 16 CORES PER CPU)

Single Intel® 4<sup>th</sup> Gen Xeon® SP CPU (Sapphire Rapids) up to 225W TDP  
Chipset: Intel® C741 Emmitsburg

## MEMORY (UP TO 2 TB)

8x DDR5-4400/4800 ECC RDIMM slots

## PCIe GEN 5.0 SLOT (CAN SUPPORT FHFL GPUs)

1x PCIe Gen 5.0 x16 slot

## I/O

- ▶ **SATA:** 8x SATA3 ports
- ▶ **USB:** 4x USB2 headers, 2x USB3 ports
- ▶ **IPMI:** IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
- ▶ **Graphics:** Intel® Integrated Graphics & ASPEED AST2600 BMC
- ▶ **Video:** 1x VGA port
- ▶ **LAN:** 3x 1GbE RJ-45 ports via dual Intel® i350 controller (1x Shared IPMI), 2x 10GbE ports
- ▶ **Serial:** 1x RS232 port

## SECURITY

### ▶ TPM 2.0

\*For a comprehensive list of cybersecurity features, please contact one of our team members.

## COOLING (BMC Controlled)

5x 4 pin system fan headers, 1x 4 pin CPU fan headers

## SYSTEM BIOS

- ▶ AMI SPI 256 Mbit BIOS
  - Plug and Play (PnP)
  - PCI 2.2
  - ACPI 1.0 / 2.0
  - USB Keyboard Support
  - SMBIOS 2.3
  - UEFI

## SYSTEM MANAGEMENT (BMC)

ASPEED AST2600 baseboard management controller: rKVM, system monitoring, out-of-band management

## OS COMPATIBILITY

- ▶ Windows Enterprise, Server
- ▶ Linux
  - RHEL
  - Ubuntu
  - SUSE

\*Contact us for the full compatibilities list

## DIMENSIONS

**Board:** 12" x 9.6" (30.48cm x 24.40cm)

**Chassis:** 19" x 1.75" x 20" (48.26cm x 4.44cm x 50.8cm)

## ENVIRONMENTAL SPECIFICATIONS

- ▶ Operating Temperature: 0°C - 50°C
- ▶ Storage Temperature: -40°C - 85°C
- ▶ Operating Humidity: 10% - 95% non-condensing
- ▶ Non-Operating Humidity: 10% - 95% non-condensing
- ▶ Shock: 3 axis, 35g, 25ms
- ▶ Vibration: 4.76Grms, 10Hz to 2000 Hz (SSD)
- ▶ Altitude: 0 to 10,000 ft (3,048m)
- ▶ Non-Operating Altitude: 0 to 30,000 ft (9,144m)

\*Preliminary numbers noted. Final numbers expected to outperform current specifications.

\*Conformal coating available upon request.

## COMPLIANCE

Designed to meet the following standards/certifications:

- ▶ MIL-STD-810H
- ▶ MIL-STD-461G
- ▶ DO-160F
- ▶ MIL-STD-704

The PT.1 Server can support multiple GPUs and other FHFL option cards. To configure a system per your requirements, reach out to a member of our team.

**Contact us for pricing and availability.**

770.287.3100 | [info@trentonsystems.com](mailto:info@trentonsystems.com)